



US010470833B2

(12) **United States Patent**
Ray

(10) **Patent No.:** **US 10,470,833 B2**

(45) **Date of Patent:** **Nov. 12, 2019**

(54) **ANESTHETIC CABLE PROTECTOR**

(56) **References Cited**

(71) Applicant: **Sheila Barrett Ray**, Harrisburg, MO
(US)

U.S. PATENT DOCUMENTS

(72) Inventor: **Sheila Barrett Ray**, Harrisburg, MO
(US)

4,114,241	A	9/1978	Bisping	
4,453,353	A	6/1984	Killop et al.	
5,944,696	A	8/1999	Bayless et al.	
6,431,216	B1	8/2002	Briscoe	
7,151,222	B1	12/2006	Jetton	
7,301,101	B2 *	11/2007	Suzuki	H02G 3/30 174/117 F

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **16/371,997**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Apr. 1, 2019**

CN	104189981	A	12/2014
EP	2150675	B1	4/2012

(65) **Prior Publication Data**

US 2019/0223970 A1 Jul. 25, 2019

OTHER PUBLICATIONS

International Search Report in International Application No. PCT/US2018/022895, dated Jul. 20, 2018 (3 pages).

(Continued)

Related U.S. Application Data

(60) Continuation of application No. 15/985,958, filed on May 22, 2018, now Pat. No. 10,285,769, which is a division of application No. 15/472,133, filed on Mar. 28, 2017, now Pat. No. 9,999,478.

Primary Examiner — Stanley Tso

(74) *Attorney, Agent, or Firm* — Benesch, Friedlander, Coplan & Aronoff LLP

(51) **Int. Cl.**

A61B 50/20 (2016.01)

A61M 16/08 (2006.01)

B65D 43/16 (2006.01)

B65D 43/22 (2006.01)

(57)

ABSTRACT

A medical safety device for holding and protecting medical circuitry connected between a medical patient and medical equipment is provided. The device can include an outer shell with an exterior sidewall and an interior sidewall defining an open interior. The outer shell can include a door that can be opened to allow access to the interior of the shell. The outer shell can include at least one latch for selectively securing the door in a closed position. The exterior shell can include connecting components for connecting the device to a hospital or surgical bed frame. The interior of the outer shell can include a grooved section having one or more grooves. The grooves can be configured to hold and retain different types of medical circuitry, such as cords, wires, tubes and the like.

(52) **U.S. Cl.**

CPC **A61B 50/20** (2016.02); **A61M 16/0875** (2013.01); **B65D 43/16** (2013.01); **B65D 43/22** (2013.01); **A61M 2209/082** (2013.01)

(58) **Field of Classification Search**

CPC **A61B 50/20**

USPC **174/68.3**

See application file for complete search history.

18 Claims, 9 Drawing Sheets

